

LITE guard by L M Products

LITE guard trench shields, the ultra light trench shoring system is now made and available in the UK, at L M Products.

The Liteguard system meets all the safety requirements of the latest British & European standards BS EN 13331.1 & .2 2002, with a Characteristic load rating of 33kNm in excess of the standard requirement of 30kNm.

This provides a working load limit of 25.5kNm for the standard LITE guard panel 2400mm long x 1200mm high, panel thickness of 45mm. A complete shield weighs in at 58kg. The shields can be stacked to 3 high providing a safe working depth of up to 4.2m including the pipe embedment zone below the shield.

The shields come with adjustable spreader bars 600mm to 900mm or 1000mm to 1800mm. Three shields stacked weigh in at approximately 400kgs we within the safe lifting capacity of a 3 to 7 tonne excavator or standard back hoe. Two people can assemble the shields on site in 2 to 3 minutes. The shields can be carried into restricted areas and assemble next to the excavation, easily transported in a small pick up, tray truck or trailer.

Great for maintenance work, or small drainage jobs, or any below ground work, from Drainage, gas, electricity, communication, storm water, sewer, or water service work.

We also have a Man hole box up to 2000mm Sq x 1800mm deep, this unit can be stacked 2 high, and again falls into the ultra light category weighing approximately 320kgs assembled.

Sales or hire contact us direct call **Mike Davies at L M Products 07970208205**, or visit the LITE guard web site at www.liteguard.com



LITE
guard

